

Elektrický lanový kladkostroj s el. pojezdem TYP T39

Typ	Nosnost (kg)	Výška zdvihu (m)	Počet lan	Rychlost zdvihu (m/min)	Zdvihový el. motor (kW)	Rychlost pojezdu (m/min)	Pojezdový el. motor (kW)	Profil pojezdových kol IPN	Radius zatáčení (m)	Hmotnost (kg)
T3933	2000	6,3	4	4	1,5	20	0,25	30-40	2,5	285
T3933M				4/0,7	1,5/0,3					315
T3943	4000	6,3	4	4	3	20	0,25	30-40	2,5	433
T3943M				4/0,7	3/0,5					520
T3944		9		4	3	20	2x0,25	30-40	2,5	650
T3944M				4/0,7	3/0,5					730
T3953	6300	6,3	4	4	4,5	20	0,37	30-40	3,5	550
T3953M				4/0,7	4,8/0,8					610
T3954		9		4	4,5	20	2x0,5	30-40	2,5	740
T3954M				4/0,7	4,8/0,8					795
T3963	10 000	6,3	4	4	8	20	2x0,37	30-40	3,5	930
T3963M				4/0,7	8/1,5					1020
T3964		9		4	8	20	2x0,37	30-40	3,5	1010
T3964M				4/0,7	8/1,5					1120
T3983	12 500	6,3	4	4	12,5	20	2x0,37	30-40	3,5	1275
T3983M				4/1,2	13/3					1350
T3984		9		4	12,5	20	2x0,37	30-40	3,5	1360
T3984M				4/1,2	13/3					1430

▣ Rozměry (mm)

Typ	Výška zdvihu (m)	Nosnost (kg)	A	D ₁	E	F	F ₂	H ₁	H _(min)	L	L ₁	L ₂	L ₄	t
T3933	6,3	2000	503	76	265	700	465	945	175	919	159	490	270	29
T3933M										949			300	
T3943	6,3	4000	503	76	265	860	545	1130	175	1010	200	510	300	29
T3943M										1080			370	
T3944	9	4000	1265	76	265	860	545	1280	175	1210	200	710	300	29
T3944M										1280			370	
T3953	6,3	6300	563	84	305	860	545	1190	175	1075	200	560	315	29
T3953M										1158			398	
T3954	9	6300	1335	76	265	860	545	1345	175	1295	200	780	315	29
T3954M										1378			398	
T3963	6,3	10 000	1188	84	305	970	620	1560	175	1102	217	540	345	35
T3963M										1177			420	
T3964	9	10 000	1398	84	305	970	620	1560	175	1312	217	750	345	35
T3964M										1387			420	
T3983	6,3	12 500	1325	84	305	1085	710	1765	150	1284	254	650	380	42
T3983M										1324			420	
T3984	9	12 500	1485	84	305	1085	710	1765	150	1444	254	810	380	42
T3984M										1484			420	